

COMPACSPREAD



Features

- Cat2 Ball Hitch With Safety Chain
- Belt Attachment Ready
- Integrated Steel Grid
- Orchard/Vineyard Spreading Kit
- Robust Parking Jack
- High-Quality Painted Mild Steel Bin And Chassis Construction

Pick Your Extras

- 3CR12 Bin Construction
- 304 Stainless Steel Bin Construction
- Rear Belt Attachment
- Single Channel Iso Bus Kit

Specifications

MODEL	RSP050-2.5GD	RSP050-2.5HD	RSP050-4.0GD	RSP050-4.0HD	RSP073-5.0G	RSP073-5.0H
LOAD CAPACITY (kg/lbs)	2500 (5511)	2500 (5511)	4000 (8818)	4000 (8818)	5000 (11023)	5000 (11023)
CAPACITY (m³/ft³)	2 (70)	2 (70)	3 (106)	3 (106)	4.5 (159)	4.5 (159)
REQ. OIL FLOW (l/min/gal/min)	50 (13.2)	50 (13.2)	50 (13.2)	50 (13.2)	50 (13.2)	110 (29)
EMPTY WEIGHT (kg/lbs)	1300 (2866)	1300 (2866)	1500 (3306)	1500 (3306)	1450 (3197)	1450 (3197)
3 SPEED GROUND RELATED GEARBOX	*		*		•	•
HYDRAULIC DRIVE GEARBOX		16:01		16:01	•	22:01
AXLE (mm/inch)	60 (2-3/8)	60 (2-3/8)	60 (2-3/8)	60 (2-3/8)	70 (2-3/4)	70 (2-3/4)
WHEELS	2 X 12.5/80-15.3	2 X 12.5/80-15.3	2 X 12.5/80-18	2 X 12.5/80-18	2 x 12.5/80-18.0	2 x 12.5/80-18.0
TRACTOR POWER REQUIREMENT (kw/hp)	45 (60)	45 (60)	56 (75)	56 (75)	56 (75)	56 (75)
A - OVERALL LENGTH (mm/inch)	4000 (157)	4000 (157)	4000 (157)	4000 (157)	6000 (236-1/4)	6000 (236-1/4)
B - DRAWBAR LENGTH (mm/inch)	1000 (39)	1000 (39)	1000 (39)	1000 (39)	1541 (60-11/16)	1541 (60-11/16)
C - BIN LENGTH (mm/inch)	2400 (94)	2400 (94)	2400 (94)	2400 (94)	3600 (141-3/4)	3600 (141-3/4)
D - REAR SECTION LENGTH (mm/inch)	800 (31)	800 (31)	800 (31)	800 (31)	800 (31-1/2)	800 (31-1/2)
E - OVERALL WIDTH (mm/inch)	2500 (98)	2500 (98)	2500 (98)	2500 (98)	1958 (77-1/16)	1958 (77-1/16)
F - BIN WIDTH (mm/inch)	1500 (59)	1500 (59)	1500 (59)	1500 (59)	1300 (51-3/16)	1300 (51-3/16)
G - WHEEL CENTRES (mm/inch)	1400 (55)	1400 (55)	1400 (55)	1400 (55)	1650 (64-15/16)	1650 (64-15/16)
H - OVERALL HEIGHT (mm/inch)	1600 (62)	1600 (62)	2000 (78)	2000 (78)	1850 (72-7/8)	1850 (72-7/8)
I - HITCH HEIGHT (mm/inch)	380-460 (15-18)	380-460 (15-18)	400-480 (16-19)	400-480 (16-19)	430 (16-15/16)	430 (16-15/16)
J - AXLE HEIGHT (mm/inch)	400 (16)	400 (16)	450 (17)	450 (17)	430 (16-15/16)	430 (16-15/16)

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
John (National) +27 83 660 1275 • Jairus (Spares) +27 79 690 4546

30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

www.radium.co.za

