

DUAL TINE RIPPER



Features

- Robust Frame Construction, from high-grade square and rectangular tubing reinforced with steel plates, ensures that torque and stresses are evenly distributed across the frame.
- Customised Row Spacing allows the machine and the planter to work in the same zone.
- Hardened Bushes on the Tine Clamp ensure that the shear angle remains constant and true.
- Universal 3-point Hitches with settings to adjust the top pin to switch between standard- and quick-hitch linkage.
- Working Depth of 900mm standard.
- Depth control wheels are standard on all models.

Pick Your Extras

- Third Shank up to 1200mm
- Row Closers
- Individual Cage Rollers
- Lister Markers
- Hydraulic Markers
- Coulters

Specifications

MODEL	RDT012	RDT022	RDT032	RDT042	RDT052	RDT062	RDT082
NO. OF ROWS	1	2	3	4	5	6	8
ROW SPACING (mm/inch)	N/A	1800 (70-7/8)	1500 (59)	910/1300 (35-7/8-51-1/16)	1500 (59)	910/1300 (35-7/8-51-1/16)	910/1300 (35-7/8-51-1/16)
DEPTH CONTROL WHEELS	2 X 6.00 X 16.0	2 X 7.50 X 16.0	2 X 7.50 X 16.0	2 X 400/60-15.5	4 X 400/60-15.5	4 X 400/60-15.5	4 X 400/60-15.5
HITCH (cat.)	III NARROW	III NARROW	III NARROW	IV NARROW	IV NARROW	IV NARROW	IV
WIDTH (mm/inch)	1648 (64-7/8)	2903 (114-5/16)	3644 (143-7/16)	394 (155-5/16)	6916 (272-1/4)	5944 (234)	9030
LENGTH (mm/inch)	1914 (75-3/8)	1914 (75-3/8)	1914 (75-3/8)	2641 (102-15/16)	3141 (123-5/8)	3141 (123-11/16)	3141 (123-11/16)
LENGTH WITH ROLLER (mm/inch)	3065 (120-11/16)	3065 (120-11/16)	3065 (120-11/16)	3791 (149-1/4)	4292 (168)	4292 (168)	429 (168)
LENGTH WITH COULTERS & ROLLER (mm/inch)	3225 (126)	3225 (126)	3225 (126)	3951 (155-9/16)	4452 (175-1/4)	4452 (175-1/4)	4452 (175-1/4)
HEIGHT (mm/inch)	1925 (75-3/4)	1925 (75-3/4)	1598 (62-15/16)	1755 (69-1/16)	1975 (77-3/4)	1719 (67-11/16)	1597 (62-7/8)
WEIGHT (kg/lbs)	426 (939)	1043 (2299)	1652 (3642)	1895 (4178)	2361 (5205)	2834 (6248)	3778 (8329)
WEIGHT WITH ROLLERS (kg/lbs)	498 (1098)	1187 (2617)	1868 (4118)	2183 (4813)	2721 (5999)	3266 (7200)	4354 (9599)
WEIGHT WITH COULTERS & ROLLER (kg/lbs)	531 (1171)	1253 (2762)	1967(4336)	2315 (5104)	2886 (6363)	3464 (7636)	4513 (9949)
WEIGHT WITH COULTERS, ROW CLOSERS & ROLLERS (kg/lbs)	577 (1272)	1345 (2965)	2105 (4641)	2499 (5509)	3116 (6869)	3740 (8245)	4986 (10992)
TRACTOR POWER REQUIREMENT (kw/hp)	65/90	135/180	195/260	260/350	325/435	375/500	450/600

● = Not Applicable ● = Standard

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
 John (National) +27 83 660 1275 • Shannon (National) + 27 76 687 1339
 Jairus (Spares) +27 79 690 4546

30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
 Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
 T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

www.radium.co.za

