

# PASTURATOR



## Features

### Robust Frame Construction

- Manufactured from high-grade square and rectangular tubing
- Reinforced with steel plates
- Torque and stresses are evenly distributed across the frame

### Universal 3-point Hitches

- Robust 3-point hitches welded onto the frame and reinforced
- Meets international ISO standards
- Adjust the top pin to switch between standard- and quick-hitch linkage

### Adjustable Tine Spacing

- Tine clamps and coulters are adjustable
- Set various row widths to suit the requirements
- Allows for tines to be added and removed
- Staggered Tine Alignment
- Improves material flow
- Prevents large clods from being brought up in dry conditions

### Various Shear Options

- Several different shears available to suit all conditions
- Easily swap around by means of a knock-on-point

## Specifications

MODEL	RPR002	RPR003	RPR004	RPR005	RPR007
NO. OF TINES	2	3	4	5	7
TINE SPACING (mm/inch)	1800 (70-7/8)	900 (35-7/16)	600 (23-5/8)	600 (23-5/8)	600 (23-5/8)
WORKING WIDTH (mm/inch)	2100 (82-11/16)	2100 (82-11/16)	2100 (82-11/16)	2700 (106-5/16)	3900 (153-9/16)
WIDTH (mm/inch)	2608 (102-11/16)	2608 (102-11/16)	2608 (102-11/16)	3208 (126-5/16)	4408 (173-9/16)
LENGTH (mm/inch)	2286 (90)	2286 (90)	2286 (90)	2286 (90)	2286 (90)
HEIGHT (mm/inch)	1213 (47-3/4)	1213 (47-3/4)	1213 (47-3/4)	1213 (47-3/4)	1213 (47-3/4)
WEIGHT (kg/lbs)	799 (1761)	899 (1982)	999 (2202)	1212 (2672)	1570 (3461)
HITCH (cat.)	III NARROW	III NARROW	III NARROW	III NARROW	III NARROW
RECOMMENDED POWER REQUIREMENT (kw/hp)	38/50	56/75	75/100	93/125	112/150

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

## CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919  
 John (National) +27 83 660 1275 • Shannon (National) + 27 76 687 1339  
 Jairus (Spares) +27 79 690 4546

[www.radium.co.za](http://www.radium.co.za)



30 3rd Street, Babelegi, Temba, North West, South Africa, 0407  
 Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400  
 T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

