

ZONETILL



Features

- Robust Frame Construction, manufactured from high-grade square and rectangular tubing, reinforced with steel plates.
- Coulter Beam adds extra strength and rigidity, reducing flex and preventing breakages.
- Accessory Beam adds extra strength and rigidity to the frame, reduces flex, prevents breakages and supports row closers and rollers.
- Customised Row Spacing allows the machine and the planter to work in the same zone.
- Depth control wheels are standard on all models

Pick your extras

- Lister Markers
- Hydraulic Markers
- Rollers
- Coulters
- Row Closers

Specifications

MODEL	RTS102	RTS103	RTS104	RTS105	RTS106
NO. OF ROWS	2	3	4	5	6
ROW SPACING (mm/inch)	760/910 (29-15/16-35-7/8)	1500/2100 (59-82-11/16)	760/910 (29-15/16-35-7/8)	1500/2100 (59-82-11/16)	760/910 (29-15/16-35-7/8)
CARRY WHEELS	•	•	•	•	•
DEPTH CONTROL WHEELS	2 X 6.00 X 16.00	2 X 7.50 X 16.00	2 X 7.50 X 16.00	4 X 7.50 X 16.00	4 X 7.50 X 16.00
HITCH (cat.)	III NARROW	III NARROW	III NARROW	III NARROW	III NARROW
WIDTH (mm/inch)	1400 (55-1/8)	4559/5860 (179-1/2/230-3/4)	3940/4319 (155-3/16-170)	7559/9960 (297-5/8-392-1/8)	4710/5460 (185-7/16-214)
TRANSPORT WIDTH (mm/inch)	1400 (55-1/8)	4559/5860 (179-1/2/230-3/4)	3940/4319 (155-3/16-170)	7559/9960 (297-5/8-392-1/8)	4710/5460 (185-7/16-214)
LENGTH (mm/inch)	3200 (126)	3200 (126)	3200 (126)	3200 (126)	3200 (126)
HEIGHT (mm/inch)	1407 (55-3/8)	1407 (55-3/8)	1407 (55-3/8)	1407 (55-3/8)	1407 (55-3/8)
WEIGHT (kg/lbs)	854 (1883)	1668/1819 (3677/4010)	1550/1885 (3417/4156)	2747/3688 (6056/8130)	2773/2844 (6113/6270)
TRACTOR POWER REQUIREMENT (kw/hp)	52/70	75/100	100/135	125/170	160/215

MODEL	RTS108	RTS110	RTS112T	RTS114T	RTS116T
NO. OF ROWS	8	10	12	14	16
ROW SPACING (mm/inch)	760/910 (29-15/16-35-7/8)	760 (29-15/16)	910 (35-7/8)	910 (35-7/8)	910 (35-7/8)
CARRY WHEELS	•	•	4 X 560/60 R 22.5	6 X 560/60 R 22.5	6 X 560/60 R 22.5
DEPTH CONTROL WHEELS	4 X 7.50 X 16.00	4 X 7.50 X 16.00	4 X 7.50 X 16.00	6 X 7.50 X 16.00	6 X 7.50 X 16.00
HITCH (cat.)	IV Narrow	IV Narrow	Trailed (CAT 4)	Trailed (CAT 4)	Trailed (CAT 4/5)
WIDTH (mm/inch)	6880/7929 (270-7/8-312-3/16)	7750 (297-1/4)	11256 (443-3/16)	13256	15256
TRANSPORT WIDTH (mm/inch)	6880/7929 (270-7/8-312-3/16)	7750 (297-1/4)	5600 (220-1/2)	5600 (220-1/2)	5600 (220-1/2)
LENGTH (mm/inch)	3200 (126)	3200 (126)	11235 (442-5/16)	11235 (442-5/16)	11235 (442-5/16)
HEIGHT (mm/inch)	1407 (55-3/8)	1407 (55-3/8)	2351 (92-9/16)	2351 (92-9/16)	2351 (92-9/16)
WEIGHT (kg/lbs)	3816/4189 (8413/9235)	4214 (9290)	10500 (23149)	12500 (27558)	14500 (31967)
TRACTOR POWER REQUIREMENT (kw/hp)	220/300	280/380	343/460	395/530	448/600

• = Not Applicable ● = Standard

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
 John (National) +27 83 660 1275 • Shannon (National) + 27 76 687 1339
 Jairus (Spares) +27 79 690 4546

30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
 Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
 T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

www.radium.co.za

