

POWERTILL



Features

- Four lever trip mechanism which trips at 7Kn force on the point.
- 150mm Cast shear
- 30mm Tine
- Working depth from 100mm to 300mm depending on soil type.
- 400mm tine pitch on 2 bar frames.
- Replaceable wear bars
- Depth control wheels are standard on all models.
- Jump height of 300mm
- Robust Frame Construction, manufactured from high-grade square and rectangular tubing, reinforced with steel plates

Pick your extras

- Rollers

Specifications

MODEL	RCP005	RCP007
NO. OF SHANKS	5	7
SHANK SPACING (mm/inch)	400 (15-3/4)	400 (15-3/4)
HITCH (cat.)	III NARROW	III NARROW
WORK WIDTH (mm/inch)	2000 (78 -3/4)	2800 (110-1/4)
WIDTH (mm/inch)	2200 (115)	3000 (118-1/5)
LENGTH (mm/inch)	2200 (86-2/3)	2200 (86-2/3)
LENGTH WITH ROLLERS (mm/inch)	3000 (118-1/5)	3000 (118-1/5)
HEIGHT (mm/inch)	1350 (53-1/5)	1350 (53-1/5)
WEIGHT (kg/lbs)	900 (1985)	1100 (2425)
WEIGHT WITH ROLLER (kg/lbs)	1200 (2645)	1600 (3525)
DEPTH CONTROL WHEELS	2 x 6.0 x 16.00	2 x 6.0 x 16.00
TRACTOR POWER REQUIREMENT (kw/hp)	65 (87)	95 (127)

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
 John (National) +27 83 660 1275 • Shannon (National) + 27 76 687 1339
 Jairus (Spares) +27 79 690 4546

30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
 Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
 T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

www.radium.co.za

