

VERTICAL FEED MIXER



Features

- Integrated Chassis means a lighter machine with greater ground clearance, without compromising on the compact design.
- Adjustable Draw Bar allows the machine to remain level with the tractor and improves tracking and ground clearance.
- Hydraulic Support Foot, fitted to the draw bar, allows effortless hitching and unhitching without the operator leaving the tractor.
- PTO Shaft is matched to the size of the machine. The shear bolt prevents any damage to the tractor or machine in case of obstructions in the mixing tank.
- Inspection Ladder is positioned in the front of the machine, allowing safe viewing of the inside.
- Remote cables are fitted to the hydraulic control bank on the machine and mounted on the tractor, making it easy for the tractor operator to reach and operate the hydraulic functions of the mixer.
- Weighing system that allows you to obtain weight of the material as well as load recipes and program off-loading points

Pick your extras

- Electro-Hydraulic Remote Control Wide Angle PTO
- Extended Discharge Conveyor
- Additional Cutting Knives
- Hydraulic Counter Knives
- Automatic Counter Knives

Specifications

Xeno

MODEL	MFX004	MFX006	MFX007	MFX009	MFX011	MFX013	MFX015	MFX018	MFX020	MFX022
CAPACITY (m ³ /ft ³)	4 (141)	6 (212)	7 (247)	9 (318)	11 (388)	13 (459)	15 (530)	18 (636)	20 (706)	22 (777)
CAPACITY (kg/lbs)	1000 (2205)	1500 (3307)	1750 (3858)	2250 (4960)	275 (6063)	3250 (7165)	3750 (8267)	4500 (9921)	5000 (11023)	5500 (12125)
LENGTH (mm/inch)	3900 (153-9/16)	4200 (165-3/8)	4400 (173-1/4)	4450 (175-3/16)	4750 (187)	4900 (192-15/16)	5150 (202-3/4)	6800 (267-3/4)	7100 (279-9/16)	7100 (279-9/16)
WIDTH (mm/inch)	2100 (82-11/16)	2100 (82-11/16)	2100 (82-11/16)	2100 (82-11/16)	2350 (929/16)	2500 (98-7/16)	2500 (98-7/16)	2100 (82-11/16)	2350 (929/16)	2350 (929/16)
HEIGHT (mm/inch)	1750 (68-7/8)	2250 (88-9/16)	2450 (96-1/2)	2700 (106-5/16)	2700 (106-5/16)	2850 (112-1/4)	2950 (116-3/16)	2700 (106-5/16)	2600 (102-3/8)	2700 (106-5/16)
EMPTY WEIGHT (kg/lbs)	2400 (5291)	2800 (6173)	3000 (6614)	3200 (7055)	3600 (7937)	4000 (8818)	4400 (9700)	6000 (13228)	6400 (14110)	6500 (14330)
WHEELS	2 X 12.5 X 15.3	2 X 30.11 R 14.5	2 X 30.11 R 14.5	2 X 30.11 R 14.5	2 X 400/60 R 15.5	2 X 400/60 R 15.5	2 X 400/60 R 15.5	2 X 435/50 R 19.5	2 X 435/50 R 19.5	2 X 435/50 R 19.5
NO. OF AUGERS	1	1	1	1	1	1	1	2	2	2
REQUIRED PTO RPM	540	540	540	540	540	540	540	540	540	540
RECOMMENDED POWER REQUIREMENT (kw/hp)	35 (50)	40 (55)	45 (60)	55 (75)	65 (90)	75 (105)	90 (120)	105 (140)	120 (160)	135 (180)

Radon Bio

MODEL	MFR016	MFR018	MFR021	MFR026	MFR030	MFR032
CAPACITY (m ³ /ft ³)	16	18	21	26	30	32
CAPACITY (kg/lbs)	4000	4500	5250	6500	7500	8000
LENGTH (mm/inch)	6100	6400	6400	8500	8600	8600
WIDTH (mm/inch)	2500	2800	2800	2500	2500	2500
HEIGHT (mm/inch)	3200	3050	3350	3000	3200	3300
EMPTY WEIGHT (kg/lbs)	5700	6000	6150	8700	9000	9200
WHEELS	2 X 400/60 R 15.5	2 X 445/45 R 19.5	2 X 445/45 R 19.5	2 X 435/50 R 19.5	2 X 435/50 R 19.5	2 X 435/50 R 19.5
NO. OF AUGERS	1	1	1	2	2	2

Due to a process of on-going product development, Radium Engineering reserves the right to change any details or specifications without prior notice

CONTACT

Kudzi (Regional) +27 72 927 1373 • Candice (Internal) +27 72 438 9919
 John (National) +27 83 660 1275 • Shannon (National) + 27 76 687 1339
 Jairus (Spares) +27 79 690 4546

www.radium.co.za



30 3rd Street, Babelegi, Temba, North West, South Africa, 0407
 Private Bag X2008, Hammanskraal, Gauteng, South Africa, 0400
 T: +27 (0) 12 719 9062/3 F: +27 (0) 12 719 9064

